

DIMENSIONS DES TURBINES pour POMPES DE REFROIDISSEMENT


Référence	Accessoires*	Réf. CEF	Photo	Insert	Ø A mm	Ø B mm	C mm	Pales
16.194.00	-	110			7,31/8	50,8	22,1	6
16.194.01	GX	100			9,5	39,6	18,94	6
16.194.02	GX	121			12	39,6	19,2	6
16.194.03	GX	101			12,17	50,8	22,1	6
16.194.04	GX	116			12,66	50,8	22,1	6
16.194.05	GT	107			14,29 / 16	57	31,6	12
16.194.06	GT	106			14,29 / 16	65	50,2	8
16.194.07	GT	105			22,4 / 25,4	96	63,1	9
16.194.08	GT	145			22,4 / 25,4	95	88,5	12
16.194.09	CGT	108			15,93 / 16	57	31,6	12
16.194.10	T	102			15,9 / 16	65	50,2	8
16.194.11	-	127			10	50,8	22,1	6

Référence	Accessoires*	Réf. CEF	Photo	Insert	Ø A mm	Ø B mm	C mm	Pales
16.194.12	-	128			17	66	32	8
16.194.13	-	129			12,7 mm	50,8 mm	22,1 mm	6
16.194.14	GT	120			15,9	65,2	41,3	12
16.194.15	GT	164			20,1	84	73,5	12
16.194.16	-	113			8	31,3	11,9	6
16.194.17	GT	103			15,9	62	31,7	12
16.194.18	HD K	187			14,29 / 16	65,2	76,65	8
16.194.19	-	380			10	39,6	14,3	12
16.194.20	X	123			12	52	25	6
16.194.21	X	131			10	39,6	19,2	6
16.194.22	-	130			8	31,75	12	6
16.194.23	-	124			14,29 / 16	57	48,2	12

Référence	Accessoires*	Réf. CEF	Photo	Insert	Ø A mm	Ø B mm	C mm	Pales
16.194.24	T	135T			22,5 / 25,4	95	63,1	10
16.194.25	T	104			14,29 / 16	57	50,2	12
16.194.26	T	114			14,29 / 16	65	50,1	10
16.194.27	G	178			14,29 / 16	57	48,2	12
16.194.28	T	112			17	65	48,6	8
16.194.29	T	109			16,85 / 19	66,5	50,6	8
16.194.31	GX-N	200			9,5	39,6	18,94	6
16.194.32	N	230			8	31,75	12	6
16.194.33	GX N	216			12,66	50,8	22,1	6
16.194.34	GT-N	205			22,5 / 25,4	96	63,1	9
16.194.35	GT-N	207			14,29 / 16	57	31,6	12
16.194.36	T-N	214			14,29 / 16	65	50,1	10

Référence	Accessoires*	Réf. CEF	Photo	Insert	Ø A mm	Ø B mm	C mm	Pales
16.194.37	GT-N	206			14,29 / 16	65	50,2	8
16.194.38	-	138			7,31 / 8	51,3	22	6
16.194.39	CGT-N	208			15,93	57	31,6	12
16.194.40	T	115			22,5 / 25,4	95	88,5	9
16.194.41	-	232			8	44,6	13	6
16.194.42	G	167			16	65	51,2	12
16.194.43	X	146			12	52	22,2	10
16.194.44	GX	156			12,7	51,8	22	10
16.194.45	-	161			22,5 / 25,4	95	63,1	12
16.194.48	G	165			15,95	62,2	22,4	12
16.194.49	-	166			12,8	56,6	19,8	12
16.194.51	-	132			8	44,6	13	6
16.194.52	-	152			20,2	95	88,5	12

Référence	Accessoires*	Réf. CEF	Photo	Insert	Ø A mm	Ø B mm	C mm	Pales
16.194.54	-	155			14,29 / 16	65	36,5	8
16.194.55	G	190			12,2	19	40	6
16.194.56	GT	189			16	57	32,05	12
16.194.57	GT	177 GT			14,29 / 16	65,2	75,65	8
16.194.59	-	185			25,4	94	63	11
16.194.60	T	186			22,5 / 25,4	96,5	130	12
16.194.62	GX	162			22,5 / 25	65,8	80	12
16.194.63								
16.194.64	GX	182			20,7	94,5	101,5	12
16.194.65	G	183			20	94,5	79,8	12
16.194.66	G	166			12,8	56,6	19,8	12
16.194.67	GT	133GT			14,29 / 16	57,18	50,25	10

Référence	Accessoires*	Réf. CEF	Photo	Insert	Ø A mm	Ø B mm	C mm	Pales
16.194.73	N	238			7,31 / 8,07	51,3	22	6
16.194.75	GX	192			20	94,5	101,5	12
16.194.77	-	144			22,5 / 25,4	117,6	8,5	9
16.194.78	G	153			20,2	117,6	88,5	9
16.194.79	-	157			13,42	57,18	50,25	10
16.194.80	G	163			22,5 / 25,4	95	95	12
16.194.81	-	172			38,82	119,7	133,10	10
16.194.82	-	148			16,85 / 19	65	50,7	10
16.194.84	CG	170			16	57	31,6	12
16.193.98	-	106GT			8	40	19	6
16.185.01	GX	100			9,5 mm	39,6 mm	18,94 mm	6
16.185.02	GX	121			12 mm	39,6 mm	19,2 mm	6
16.185.03	GX	101			12 mm	50,8 mm	22,1 mm	6

16.185.05	GT	107			16 mm	57 mm	31,6 mm	12
16.185.06	GT	500106			16 mm	65 mm	50,2 mm	8
16.185.07	GT	105			25,4 mm	95 mm	63,1 mm	9
16.185.26	T	114			16 mm	65 mm	50,1 mm	8
16.185.13	-	129			12,7 mm	50,8 mm	22,1 mm	6
16.186.73	N	238			8,07 mm	51 mm	22 mm	6

Accessoires:

G: joint

GT: joint + bouchon

GX: joint + écrou

X: écrou

CGT: clé + joint + bouchon

N: caoutchouc nitrile résistant aux huiles